

Treo Rig #23 Specifications

- Capable of drilling to a depth of 600 m
- Able to run Range 3 casing
- 9 m drill pipe
- Equipped with coring assembly and wireline retrieval system
- Pason recording system with electronic PVT
- Rig crew consists of four crew members per 12-hour shift supervised by a 24-hour rig manager

RIG AND SUPPORTING EQUIPMENT

Rig:

- 2001 series truck-mounted drill rig
- Self-mobile

Substructure:

- 1 m height
- Heated cellar

Mud Pump:

- Gardner Denver PAH 375 Triplex
- 350 hp
- Skid mount

Mud Tank:

- 25 m³
- Three compartments including trip tank
- Electronic PVT
- Shale shaker
- Mixing pump
- Mixing hopper
- Skid mount

Generator/Fuel Storage Building:

- 90 kw Isuzu
- 6,000 litres fuel storage with pump
- Skid mount

Blowout Preventer Configuration:

- Class I
- 7" Reagan Taurus
- 6" 150 psi H.C.R.

Boiler:

- 60 hp Scotch fire tube boiler
- Skid mount

Pipe Trailer:

- 9 m core pipe
- 9 m 7" heavy weight collar
- 9 m 5" heavy weight collar
- Trailer mount

Core Trailer/Dog House Combo Shack:

- Heated core bench
- All required coring equipment
- Rig tools
- Pintle hitch

Supervisor's Well Site Trailer:

- Pintle hitch wheeled trailer
- Single-occupancy

Flare Tank:

- 10 m³ tank
- All required flare line and piping
- Skid mount

Additional Equipment:

- Crew truck
- Pick-up for rig manager
- Two hydraulic trash pumps